Fiber laser cutting machine

LaserTWO

COST-EFFICIENT LASER CUTTING

Why LaserTWO?

- Lowest cost per part
- Full range of power sources available

VLVD

- · Reliable performance
- Optional covers and shuttle bed



LVDGROUP.COM

LaserTWO

COST-EFFICIENT LASER CUTTING

Designed with a modular, no-nonsense approach, LaserTWO strikes the perfect balance between price and functionality. The fiber laser is available in three modular configurations to fit your price-performance needs.



NO COVERS SIMPLICITY MEETS FUNCTIONALITY

The most basic LaserTWO model offers laser cutting at the lowest price point and combines high cutting speed and precision. This single bed machine is available for non-CE markets only.

HIGHLIGHTS

Cost-effective cutting

LaserTWO is the ideal solution for bringing laser cutting in-house for greater quality control, higher productivity and profits, without compromising your budget.



LOCAL COVERS SAFETY FIRST

Local covers and light guards ensure operator safety while maintaining high performance. The cutting zone has a cover that can be opened for maintenance, check-ups, part evacuation. Windows at the sides ensure visibility of the laser cutting process. With a handheld control unit the operator can safely move all axes for setup.

NC focus cutting head

Featuring auto focus with 7.8" (200 mm) focusing lens, capacitive height sensor and crash protection, LaserTWO provides the flexibility to process a wide variety of materials and thicknesses.

Modular machine

LaserTWO can be built up from a basic no-cover version to a fully enclosed model to match different priceperformance needs.

Reliable performance

The machine construction and key components such as power source, cutting head, control and drive system assure proven, reliable performance.

Quick scrap removal

Scrap bins underneath the exhaust unit can easily be removed.



FULL COVERS AND SHUTTLE BED MAXIMIZED EFFICIENCY

The full cover version with integrated shuttle tables takes performance to the next level, making loading and unloading fast and practical, and enabling seamless integration with LA Load automation for even areater efficiency.



DISCOVER LaserTWO

OPTIONS

Shuttle table for enhanced productivity

Add the option "full covers and shuttle tables" to provide maximum operator safety and increase machine productivity. The shuttle table changeover is completed in just 30 seconds.

MOVit Load-Assist (LA)

With shuttle tables, LaserTWO perfectly combines with LVD's MOVit LA Load to transfer unprocessed sheets to the machine shuttle table.

SPECIFICATIONS

	LaserTWO 3015	
Machine specifications		
Maximum sheet size	120" x 60" (3050 x 1525 mm)	
X-axis travel	125" (3185 mm)	
Y-axis travel	61" (1560 mm)	
Z-axis travel	3.1" (80 mm)	
Maximum sheet weight on table	1,984 lbs. (900 kg)	
Maximum positioning speed X-Y	4,330"/min. (110 m/min)	
Maximum positioning speed Z	1,181"/min (30 m/min)	
Repetitive accuracy	± 0.002" (0.050 mm)	
Positioning accuracy**	± 0.003" (0.10 mm)	
Shuttle bed	on full cover version	
Machine dimensions no cover version	(excluding light guards, filter and chiller)	
Length	16.4 ft (5000 mm)	
Width	9.5 ft (2900 mm)	
Height	5.8 ft (1780 mm)	

"With a full range of powers available, the system gives you the flexibility to bring laser cutting in-house and optimize your cost per part."

	3 kW	6 kW	12 kW
Laser power			
Maximum cutting performance			
Mild steel	5/8" (15 mm)	1.0" (25 mm)	1.25" (30 mm)
Stainless steel	1/2" (12 mm)	3/4" (20 mm)	1.25" (30 mm)
Aluminum	1/2" (12 mm)	1.0" (25 mm)	1.25" (30 mm)
Copper	1/4" (6 mm)	5/16" (8 mm)	5/8" (15 mm)
Brass	3/16" (5 mm)	5/16" (8 mm)	5/8" (15 mm)

Specifications subject to change without prior notice.



^{*} Achievable workpiece accuracy depends on the type of workpiece, pre-treatment and sheet size, as well as other variables. According to VDI/DGQ 3441.